

**Product information on solid fuel local space heaters
according to Commission regulation (EU) 2015/1185**



| | |
|---|---|
| Model | HWAM 2610, HWAM 2620, HWAM 2630, HWAM 2640 |
| Direct heat output [kW] | 4,5 |
| Indirect heating functionality | No |
| Indirect heat output [kW] | - |
| Type of heat output/room temperature control | Two or more manual stages, no temperature control |

| Space heating performance at nominal heat output | | |
|--|---|--|
| Fuel | Preferred fuel | Seasonal space heating energy efficiency [%] |
| Wood logs with moisture content 12-18 % | Yes | 70,3 |
| Emissions | mg/m³ (13% O₂) | |
| Particulate matter (PM) | 22 | |
| Organic gaseous compounds (OGC) | 96 | |
| Carbon monoxide (CO) | 1250 | |
| Nitrogen oxides (NO _x) | 121 | |

| Characteristics when operating with the preferred fuel only | |
|---|------|
| Nominal heat output [kW] | 4,5 |
| Electric power consumption nominal heat output [kW] | - |
| Electric power consumption minimum heat output [kW] | - |
| Electric power consumption standby mode [kW] | - |
| Useful efficiency at nominal heat output [%] | 80,3 |
| Energy efficiency index | 106 |
| Energy efficiency class | A |

Specific Precautions during Assembling, Installing & Maintenance:

See installation instructions for more information

Product End-of-Life/Recycling:

To dispose of the stove after the product life has expired, please observe the following information

- Dispose of the items correctly i.e. separate the parts to be disposed of in material groups
- Always dispose of items in a way that is as sustainable as possible and that is in line with the current environmental protection, reprocessing/recycling and disposal technology