

**Product information on solid fuel local space heaters
according to Commission regulation (EU) 2015/1185**



Model	HWAM 4510 IHS, HWAM 4520 IHS, HWAM 4530 IHS, HWAM 4540 IHS, HWAM 4550 IHS, HWAM 4560 IHS
Direct heat output [kW]	4,9
Indirect heating functionality	No
Indirect heat output [kW]	-
Type of heat output/room temperature control	With electronic room temperature control

Space heating performance at nominal heat output		
Fuel	Preferred fuel	Seasonal space heating energy efficiency [%]
Wood logs with moisture content 12-18 %	Yes	71
Emissions	mg/m³ (13% O₂)	
Particulate matter (PM)	19	
Organic gaseous compounds (OGC)	37	
Carbon monoxide (CO)	750	
Nitrogen dioxide (NO ₂)	92	

Characteristics when operating with the preferred fuel only	
Nominal heat output [kW]	4,9
Electric power consumption nominal heat output [kW]	0,015
Electric power consumption minimum heat output [kW]	0,012
Electric power consumption standby mode [kW]	0,0015
Useful efficiency at nominal heat output [%]	81
Energy efficiency index	107
Energy efficiency class	A+

Specific Precautions during Assembling, Installing & Maintenance:

See installation instructions for more information

Product End-of-Life/Recycling:

To dispose of the stove after the product life has expired, please observe the following information

- Dispose of the items correctly i.e. separate the parts to be disposed of in material groups
- Always dispose of items in a way that is as sustainable as possible and that is in line with the current environmental protection, reprocessing/recycling and disposal technology